





Computerized Lockstitch Machine With Electronic Control Stitch Length System







FRANCE GÉNÉRAL MACHINES À COUDRE

Réparation • Vente • Achat • Location




Germany design, Unique image, precise details



1 High precision stitch

stitch length can reach 0.1mm controlled by stepping motor. Stitch length adjustment function can be locked just in case operator's mis-operation.






2 High stitch overlapping ratio

Overlapping stitch can be perfectly realise in any stitch length, front and back thread remaining lock function is available.

FRANCE GENERAL MACHINES A COUDRE 13 Chemin du Génie 69200 Vénissieux Tél: +33(0) 4 78 68 66 62 + 33(0)6 45 58 79 03 E mail: contact@fgmc.pro https://francegeneralmachinesacoudre.fr




3 variable stitches, fashionable and beautiful

Different sewing stitch is available based on different clothes requirements. And editable pattern enables more fashionable and beautiful stitches.



5 Short thread remaining, no need to trim again

No need ta trim thread remaining again, which avoids trimming risks and save labour, time and money.



4 Noiseless reverse sewing, quiet and comfortable

Stepping motor controlled reverse sewing structure by scientific design achieves noiseless reverse sewing, which enables a quiet and comfortable environment.



6 Super USB port

Innovated USB port can not only charge phone, but also run fan and upgrade software.

Specification

Mode!	Needle	Thread Number	Max Stitch Length (mm)	Presser Foot Lifter Height (mm)	Max Speed (s.p.m)	Thin/ medium thick	Thick material	Volume (mm)	Weight (kg)
A4E	DBx111-1B#	2	5	5-13	5500	V	/	695x295x550	41/47
A4E-H-M	DBx111-18#	2	5	5-13	5500	V	/	695x295x550	41/47
A4E-H	DPxS 18-21#	2	5	5-13	3500	V	V	695x295x550	41/47
A4E-CP	DBx111-18#	2	5	5-13	5500	V	/	695X295X550	41/47

NOTE, Stand configuration is powermax contrai box, and Q(Qixing) contrai box is also available. Japanese hook, auto trimmer, auto reverse sewing, auto presser foot lifter, electronic tension post, Smm stitch length, 7mm stitch length is optional, P means multiples of 1.6 hook

WWW.FGMC.PRO